



Richmond, May 29th 2023

TurboMax - New designs. Same outstanding benefits.

Thermo 2000 is pleased to announce a complete update of its **TurboMax** line, which now includes eight models instead of eleven.

In addition to a new look, the instantaneous indirect hot water heater features two additional standard connections, increased tank volume, improved insulation, and a better copper flange design.

No compromise has been made in order to offer these new features while guaranteeing maximum durability and performance. Below, you will find a comparative table of the main characteristics to understand the equivalence.

Specifications

WAS → → →				NEW			
Model	Max. pressure	Tank Volume	Exchange surface	Model	Max. pressure	Tank Volume	Exchange surface
TurboMax 23	150 psi	26 gal	19.6 ft2	TurboMax 30-3	150 psi	30 gal	19.6 ft2
TurboMax 24	150 psi	26 gal	26.2 ft2				
TurboMax 33	150 psi	36 gal	19.6 ft2				
TurboMax 34	150 psi	36 gal	26.2 ft2				
TurboMax 43	150 psi	48 gal	19.6 ft2	TurboMax 50-3	150 psi	50 gal	19.6 ft2
TurboMax 44	150 psi	48 gal	26.2 ft2				
TurboMax 45	150 psi	48 gal	32.7 ft2	TurboMax 50-5	150 psi	50 gal	32.7 ft2
TurboMax 65	150 psi	72 gal	32.7 ft2	TurboMax 80-5	150 psi	80 gal	32.7 ft2
TurboMax 65A*	150 psi	67 gal	32.7 ft2	TurboMax 80-5A*	150 psi	80 gal	32.7 ft2
TurboMax 109	150 psi	119 gal	58.9 ft2	TurboMax 120-9	150 psi	119 gal	58.9 ft2
TurboMax 109A*	200 psi	110 gal	58.9 ft2	TurboMax 120-9A 200*	200 psi	120 gal	58.9 ft2
				TurboMax 120-9A 125*	125 psi	120 gal	58.9 ft2

* Models built in conformity to the ASME standard